Hans Saurer Kugellager AG
Niederfeld 38
CH-9320 Stachen

# data sheet

## general data/description

created: 09.12.2014 / 02




**article** GLY.PG 202325 F **Art-No.** 36083 **brand** SKA **weight/kg** 0.019

**remark** Dimensions and tolerances according ISO 3547-1, controls according ISO 3547-2. Recommended housing receiving bore: Tolerance H7. Shaft according to required clearance.

**description**

| | |
|---|---|
| GLY.PG | Design |
| 202325 | Size |
| F | Sliding layer, maintenance-free |

## dimensions and tolerances




| dimension | Description | [mm] | tolerance [µm] | DIN/ISO |
|---|---|---|---|---|
| Di | nominal inner diameter | 20 | | 3547-1 |
| Do | nominal outer diameter | 23 | 35 / 75 | 3547-1 |
| B | width | 25 | -300 / 0 | WERKSNORM |
| s3 | wall thickness | 1.5 | -25 / 5 | 3547-1 |

## calculation and operating data

| | | | | | |
|---|---|---|---|---|---|
| **load ratings** | **dynamic C [N]** | **fatique load limit load Cu [N]** | **DIN/ISO** | **static Co [N]** | **DIN/ISO** |
| | 39000 | | | 120000 | |
| **operating temperature** | **max. [°C]** | **min. [°C]** | | | |
| | 250 | -195 | | | |
| **bearing clearance** | **radial min. [µm]** | **max. [µm]** | | | |
| | 10 | 112 | | | |

## material specification

| description | material | DIN/ISO | hardness |
|---|---|---|---|
| Slide coating | PTFE | | |
| Supporting material | Bronze - Powder | | |
| Envelope | Sheet steel | | |
| Outside coating | Copper - Tin | | |

All information in this document was provided and checked carefully. Nevertheless, we can not assume any liability for incomplete or faulty information.