general data/description

created: 18.08.2015 / 04 page: 1 / 2

article UCF 204 H6 HA2 **Art-No.** 43432 **brand** SKA **weight/kg** 0.59

remark Rotational speed is reference value for shaft tolerance h7. Also depending on load and seal.


description

UCF	Design
204	Size
H6	Tolerance outside diameter

greasing

HA2	HANGU2#, GREAT WALL MOTOR BEARING GREASE

dimensions and tolerances



dimension	Description	[mm]	tolerance [µm]	DIN/ISO
d	nominal inner diameter	20	0 / 18	626-1
D	nominal outer diameter	47	0 / 16	SONDER
B	inner ring width	31		626-1
C	outer ring width	17	0 / -120	626-1
S	swing axle distance	12.7		626-1
A	housing width	25.5		626-2
A1	flange thickness	12		626-2
A2	effect distance	15	-500 / 500	626-2
A3	total width	33.3		
J	hole spacing	64	-500 / 500	626-2
L	housing length	86		626-2
N	hole diameter	12		
sw	wrench size	3		
G	thread	M6x0.75		

calculation and operating data

load ratings	dynamic C [N]	fatique load limit load Cu [N]	DIN/ISO	static Co [N]	DIN/ISO
	12800		281	6410	76

speed of rotation limit	reference n [1/min]	grease n [1/min]	oil n [1/min]
		5300	

operating temperature	max. [°C]	min. [°C]
	120	-20

bearing clearance	radial min. [µm]	max. [µm]
	13	28

Hans Saurer Kugellager AG
Niederfeld 38
CH-9320 Stachen

article UCF 204 H6 HA2 **Art-No.** 43432

material specification

description	material	DIN/ISO	hardness
Inner ring	100Cr6	683-17	58-65
Outer ring	100Cr6	683-17	58-65
Balls	100Cr6	683-17	58-65
Cage	Sheet steel		
Seals	Sheet steel/NBR		
Centrifugal disc	Sheet steel		
Housing	GG20		

All information in this document was provided and checked carefully. Nevertheless, we can not assume any liability for incomplete or faulty information.