general data/description

created: 08.08.2019 / 02 page: 1 / 2

article UBPFL 204 VERZ HA2 **Art-No.** 43445 **brand** SKA **weight/kg** 0.21

remark Rotational speed is reference value for shaft tolerance h7. Also depending on load and seal. Not relubricatable.


description

UBPFL	design
204	Size
VERZ	galvanized

greasing

HA2	HANGU2#, GREAT WALL MOTOR BEARING GREASE

dimensions and tolerances



dimension	Description	[mm]	tolerance [µm]	DIN/ISO
d	nominal inner diameter	20	0 / 18	626-1
D	nominal outer diameter	47	0 / -11	620-2
B	inner ring width	25	0 / -120	620-2
C	outer ring width	14	0 / -120	620-2
rs min.	minimal chamfer dimension	1		616
S	swing axle distance	7		626-1
A	housing width	16		626-2
A1	flange thickness	4		626-2
J	square hole distance	71.5	-400 / 400	626-2
N	square hole	9	-600 / 600	626-2
H	housing length	90		626-2
L	housing width	67		626-2
H2 min.	connection diameter	56		
G	thread	M5x0.8		
sw	wrench size	2.5		

article UBPFL 204 VERZ HA2 **Art-No.** 43445

calculation and operating data

load ratings	**dynamic C [N]**	**fatique load limit load Cu [N]**		**DIN/ISO**	**static Co [N]**	**DIN/ISO**
	12800	340		281	6590	76
speed of rotation limit	**reference n [1/min]**	**grease n [1/min]**	**oil n [1/min]**			
		2400				
operating temperature	**max. [°C]**	**min. [°C]**				
	120	-20				
bearing clearance	**radial min. [µm]**	**max. [µm]**				
	13	28				

material specification

description	material	DIN/ISO	hardness
Inner ring	100Cr6	683-17	58-65
Outer ring	100Cr6	683-17	58-65
Balls	100Cr6	683-17	58-65
Cage	Sheet steel		
Seals	Sheet steel/NBR		
Housing	Sheet steel		

All information in this document was provided and checked carefully. Nevertheless, we can not assume any liability for incomplete or faulty information.