Hans Saurer Kugellager AG
Niederfeld 38
CH-9320 Stachen

data sheet

general data/description

article NUKR 52 SK LX3 **Art-No.** 44580 **brand** SKA **weight/kg** 0.465

remark Tragzahlen gerechnet nach Normen für Wälzlager. Drehzahlen für F < 0.05 C0.


description

NUKR	Design
52	Size
SK	Hexagon socket

greasing

LX3	SHELL GADUS S3 V220C 2

dimensions and tolerances



dimension	Description	[mm]	tolerance [µm]	DIN/ISO
d1	shaft diameter	20	0 / -21	
d2	inner shoulder diameter	31		
d3	diameter lubrication hole	4		
D	nominal outer diameter	52	0 / -50	
C	outer ring width	24	0 / -120	620-2
C1	distance	0.8		
B	length	66	-300 / 600	
B1 max.	width	25.6		
B2	shaft lenght	40.5		

article NUKR 52 SK LX3 **Art-No.** 44580

dimension	Description	[mm]	tolerance [µm]	DIN/ISO
B3	distance lubrication hole	9		
R	radius outer ring	OP		
rs min.	minimal chamfer dimension	1		
G	thread	M20x1.5		
LG	thread length	21		
sw	wrench size	10		

calculation and operating data

load ratings	dynamic C [N]	fatique load limit load Cu [N]	DIN/ISO	static Co [N]	DIN/ISO
	43000	7400	281	58000	76

speed of rotation limit	reference n [1/min]	grease n [1/min]	oil n [1/min]
		3200	

operating temperature	max. [°C]	min. [°C]
	120	-20

bearing clearance	radial min. [µm]	max. [µm]
	0	25

material specification

description	material	DIN/ISO	hardness
Outer ring	100Cr6	683-17	58-65
Roller stud	16CrMo4		
Cylindrical rollers	100Cr6	683-17	58-65
Axial washer	100Cr6	683-17	58-65
Seals	Sheet steel		

All information in this document was provided and checked carefully. Nevertheless, we can not assume any liability for incomplete or faulty information.