general data/description


created: 15.07.2015 / 05 page: 1 / 2

article NJ 213 E TVP2 HQS C3 **Art-No.** 46316 **brand** SKA **weight/kg** 1.03

description

NJ	Design
213	Size
E	Reinforced version
TVP2	Plastic cage
HQS	Material
C3	Internal clearance

dimensions and tolerances



dimension	Description	[mm]	tolerance [µm]	DIN/ISO
d	nominal inner diameter	65	0 / -15	620-2
D	nominal outer diameter	120	0 / -15	620-2
B	width	23	0 / -150	620-2
r1s min.	minimal chamfer dimension	1.5		5412-1
r2s min.	minimal chamfer dimension	1.5		5412-1
Fw	inner enveloping circle diameter	78.5	0 / 20	5412-1
E	raceway diameter outer ring	108.5		5412-1
d1	inner shoulder diameter	84.6		
D1	outer shoulder diameter	104		
s	axial displacement	~ 1.5		
C3	internal clearance	0.06 / 0.09		620-4

calculation and operating data

load ratings	dynamic C [N]	fatique load limit load Cu [N]	DIN/ISO	static Co [N]	DIN/ISO
	107000	14800	281	119000	76

speed of rotation limit	reference n [1/min]	grease n [1/min]	oil n [1/min]
		4800	5600

operating temperature	max. [°C]	min. [°C]
	120	-20

bearing clearance	radial min. [µm]	max. [µm]
	60	90

material specification

description	material	DIN/ISO	hardness
Inner ring	100Cr6	683-17	58-65
Outer ring	100Cr6	683-17	58-65
Cylindrical rollers	100Cr6	683-17	58-65
Cage	PA66 + GF25		

Hans Saurer Kugellager AG
Niederfeld 38
CH-9320 Stachen

article NJ 213 E TVP2 HQS C3 **Art-No.** 46316

All information in this document was provided and checked carefully. Nevertheless, we can not assume any liability for incomplete or faulty information.