Hans Saurer Kugellager AG
Niederfeld 38
CH-9320 Stachen

general data/description


created: 08.09.2015 / 05 page: 1 / 2

article NUP 308 E M1 HQS **Art-No.** 46488 **brand** SKA **weight/kg** 0.782

description

NUP	Design
308	Size
E	Reinforced version
M1	Brass cage, roller centered
HQS	Material

dimensions and tolerances



dimension	Description	[mm]	tolerance [µm]	DIN/ISO
d	nominal inner diameter	40	0 / -12	620-2
D	nominal outer diameter	90	0 / -15	620-2
B	width	23	0 / -120	620-2
Fw	inner enveloping circle diameter	52	0 / 15	5412-1
r1s min.	minimal chamfer dimension	1.5		5412-1
r2s min.	minimal chamfer dimension	1.5		5412-1
D1	outer shoulder diameter	75.4		
d1	inner shoulder diameter	57.7		
E	raceway diameter outer ring	80		
B1	flange width	4		5412-1

article NUP 308 E M1 HQS **Art-No.** 46488

calculation and operating data

load ratings	**dynamic C [N]**	**fatique load limit load Cu [N]**		**DIN/ISO**	**static Co [N]**	**DIN/ISO**
	80300	9600		281	78400	76
speed of rotation limit	**reference n [1/min]**	**grease n [1/min]**	**oil n [1/min]**			
		6700	8000			
operating temperature	**max. [°C]**	**min. [°C]**				
	120	-20				
bearing clearance	**radial min. [µm]**	**max. [µm]**				
	25	50				

material specification

description	material	DIN/ISO	hardness
Inner ring	100Cr6	683-17	58-65
Outer ring	100Cr6	683-17	58-65
Cylindrical rollers	100Cr6	683-17	58-65
Cage	CuZn40Pb2		
Flange disc	100Cr6	683-17	58-65

All information in this document was provided and checked carefully. Nevertheless, we can not assume any liability for incomplete or faulty information.