Hans Saurer Kugellager AG
Niederfeld 38
CH-9320 Stachen

data sheet

general data/description

created: 17.01.2020 / 02

article NATV 6 PP OP LX3 **Art-No.** 46580 **brand** SKA **weight/kg** 0.021

remark Load ratings calculated according norms for rolling bearings. Rotational speed for F < 0.05 C0rw.


description

NATV	Design
6	Size
PP	Seals on both sides
OP	Optimized profile

greasing

LX3	SHELL GADUS S3 V220C 2


dimensions and tolerances



Einbau (Prinzipdarstellung)

Installation (représentation schématique)

Installation (schematic diagram)



dimension	Description	[mm]	tolerance [µm]	DIN/ISO
d	nominal inner diameter	6	0 / -8	620-2
D	nominal outer diameter	19	0 / -50	WERKSNORM
d2	axial washer outer diameter	15		
B	inner ring width	12	0 / -180	WERKSNORM
C	outer ring width	11	0 / -120	620-2
rs min.	minimal chamfer dimension	0.15		ISO 7063
R	radius outer ring	OP		
Crw [N]	Effective dynamic load rating	5850		
C0rw [N]	Effective static load rating	6680		
Curw [N]	Effective fatigue limit load	637		

calculation and operating data

load ratings	dynamic C [N]	fatique load limit load Cu [N]	DIN/ISO	static Co [N]	DIN/ISO
	7920	1470	281	10300	76

speed of rotation limit	reference n [1/min]	grease n [1/min]	oil n [1/min]
		3100	

operating temperature	max. [°C]	min. [°C]
	100	-20

bearing clearance	radial min. [µm]	max. [µm]
	10	35

Hans Saurer Kugellager AG
Niederfeld 38
CH-9320 Stachen

article NATV 6 PP OP LX3 **Art-No.** 46580

material specification

description	material	DIN/ISO	hardness
Inner ring	100Cr6	683-17	58-65
Outer ring	100Cr6	683-17	58-65
Needle rollers	100Cr6	683-17	58-65
Seals	PA66		
Axial washers	100Cr6	683-17	58-65

All information in this document was provided and checked carefully. Nevertheless, we can not assume any liability for incomplete or faulty information.