Hans Saurer Kugellager AG
Niederfeld 38
CH-9320 Stachen

data sheet

general data/description

created: 30.10.2015 / 04 page: 1 / 1

article NU 2210 E TVP2 BN3 **Art-No.** 46624 **brand** SKA **weight/kg** 0.575


description

NU	Design
2210	Size
E	Reinforced version
TVP2	Plastic cage

greasing

BN3	KLÜBER STABURAGS NBU 12

dimensions and tolerances



dimension	Description	[mm]	tolerance [µm]	DIN/ISO
d	nominal inner diameter	50	0 / -12	620-2
D	nominal outer diameter	90	0 / -15	620-2
B	width	23	0 / -120	620-2
Fw	inner enveloping circle diameter	59.5	0 / 15	5412-1
r1s min.	minimal chamfer dimension	1.1		5412-1
r2s min.	minimal chamfer dimension	1.1		5412-1
D1	outer shoulder diameter	78.3		WERKSNORM
E	raceway diameter outer ring	81.5		

calculation and operating data

load ratings	dynamic C [N]	fatique load limit load Cu [N]	DIN/ISO	static Co [N]	DIN/ISO
	78200	11300	281	90000	76

speed of rotation limit	reference n [1/min]	grease n [1/min]	oil n [1/min]
		6300	8000

operating temperature	max. [°C]	min. [°C]
	120	-20

bearing clearance	radial min. [µm]	max. [µm]
	30	60

material specification

description	material	DIN/ISO	hardness
Inner ring	100Cr6	683-17	58-65
Outer ring	100Cr6	683-17	58-65
Cylindrical rollers	100Cr6	683-17	58-65
Cage	PA66 + GF25		

All information in this document was provided and checked carefully. Nevertheless, we can not assume any liability for incomplete or faulty information.