
general data/description

created: 29.03.2019 / 02 page: 1 / 2

article B 71903 C T U L P4S **Art-No.** 47108 **brand** SKA **weight/kg** 0.072

description	
B	Design
71903	Size
C	Pressure angle
T	Hard tissue cage
U	Universally pairable
L	Slight preload
P4S	Tolerance class

dimensions and tolerances



dimension	Description	[mm]	tolerance [µm]	DIN/ISO
d	nominal inner diameter	17	0 / -4	620-2
D	nominal outer diameter	30	0 / -5	620-2
B	width	7	0 / -80	620-2
r1s min.	minimal chamfer dimension	0.3		628-6
r2s min.	minimal chamfer dimension	0.1		628-6
a	load application point	6.6		
alpha	contact angle	15°		628-6
Fv	pretension [N]	20		
c	axial stiffness [N/µm]	17.5		
KaE	Lift-off force [N]	62		

calculation and operating data

load ratings	dynamic C [N]	fatique load limit load Cu [N]	DIN/ISO	static Co [N]	DIN/ISO
	5300	236	281	2230	76

speed of rotation limit	reference n [1/min]	grease n [1/min]	oil n [1/min]
		50000	80000

operating temperature	max. [°C]	min. [°C]
	120	-20

material specification

description	material	DIN/ISO	hardness
Inner ring	100Cr6	683-17	58-65
Outer ring	100Cr6	683-17	58-65
Balls	100Cr6	683-17	58-65
Cage	PF		

Hans Saurer Kugellager AG
Niederfeld 38
CH-9320 Stachen

article B 71903 C T U L P4S **Art-No.** 47108

All information in this document was provided and checked carefully. Nevertheless, we can not assume any liability for incomplete or faulty information.