general data/description


created: 23.12.2020 / 01 page: 1 / 2

article RA 15008C CC0 **Art-No.** 47444 **brand** SKA **weight/kg** 0.20

description

RA	Design
15008C	Size
CC0	Internal clearance

dimensions and tolerances



dimension	Description	[mm]	tolerance [µm]	DIN/ISO
d	nominal inner diameter	150	-25 / 0	620-2
D	nominal outer diameter	166	-25 / 0	620-2
B	width	8	-120 / 0	620-2
r min.	minimal chamfer dimension	0.5		
d0	diameter lubrication hole	1.5		
ds max.	mounting dimension	153.5		
Dh min.	mounting dimension	160.5		
dpw	Roll center circle	157		
Ca [N]	dynamic load rating, axial	9920		
C0a [N]	static load capacity, axial	49200		
Cua [N]	fatigue limit load, axial	4500		

calculation and operating data

load ratings	dynamic C [N]	fatique load limit load Cu [N]	DIN/ISO	static Co [N]	DIN/ISO
	8800	2205	281	19700	76

speed of rotation limit	reference n [1/min]	grease n [1/min]	oil n [1/min]
		440	630

operating temperature	max. [°C]	min. [°C]
	120	-20

bearing clearance	radial min. [µm]	max. [µm]
	-8	0

article RA 15008C CC0 **Art-No.** 47444

material specification

description	material	DIN/ISO	hardness
Inner ring	100Cr6	683-17	58-65
Outer ring	100Cr6	683-17	58-65
Cylindrical rollers	100Cr6	683-17	58-65
Spacer	PA1010		

All information in this document was provided and checked carefully. Nevertheless, we can not assume any liability for incomplete or faulty information.