Hans Saurer Kugellager AG
Niederfeld 38
CH-9320 Stachen

data sheet

general data/description

created: 05.03.2018 / 04 page: 1 / 1


article B 7006 C T P4S UL **Art-No.** 47536 **brand** SKA **weight/kg** 0.132

remark Tolerance class P4S: dimensional accuracy P4, running accuracy P2, according DIN 620-2.

description

B	Design
7006	Size
C	Pressure angle
T	Hard tissue cage
P4S	Tolerance class

dimensions and tolerances



dimension	Description	[mm]	tolerance [µm]	DIN/ISO
d	nominal inner diameter	30	0 / -5	620-2
D	nominal outer diameter	55	0 / -7	620-2
B	width	13	0 / -120	620-2
r1s min.	minimal chamfer dimension	1		616
r2s min.	minimal chamfer dimension	1		SONDER
a	load application point	~12.3		
alpha	contact angle	15°		
Fv	pretension [N]	74		
c	axial stiffness [N/µm]	32.4		
KaE	Lift-off force [N]	228		

calculation and operating data

load ratings	dynamic C [N]	fatique load limit load Cu [N]	DIN/ISO	static Co [N]	DIN/ISO
	16800	535	281	10260	76

speed of rotation limit	reference n [1/min]	grease n [1/min]	oil n [1/min]
		28000	43000

operating temperature	max. [°C]	min. [°C]
	120	-20

material specification

description	material	DIN/ISO	hardness
Inner ring	100Cr6	683-17	58-65
Outer ring	100Cr6	683-17	58-65
Balls	100Cr6	683-17	58-65
Cage	PF		

All information in this document was provided and checked carefully. Nevertheless, we can not assume any liability for incomplete or faulty information.