Hans Saurer Kugellager AG
Niederfeld 38
CH-9320 Stachen

data sheet

general data/description


created: 11.07.2016 / 03 page: 1 / 1

article NU 2213 E TVP2 **Art-No.** 47659 **brand** SKA **weight/kg** 1.41

description

NU	Design
2213	Size
E	Reinforced version
TVP2	Plastic cage

dimensions and tolerances



dimension	Description	[mm]	tolerance [µm]	DIN/ISO
d	nominal inner diameter	65	0 / -15	620-2
D	nominal outer diameter	120	0 / -15	620-2
B	width	31	0 / -150	620-2
Fw	inner enveloping circle diameter	78.5	0 / 20	5412-1
r1s min.	minimal chamfer dimension	1.5		5412-1
r2s min.	minimal chamfer dimension	1.5		5412-1
s	axial displacement	~ 1.9		
D1	outer shoulder diameter	~ 104		
E	raceway diameter outer ring	108.5		

calculation and operating data

load ratings	dynamic C [N]	fatique load limit load Cu [N]	DIN/ISO	static Co [N]	DIN/ISO
	151000	23000	281	184000	76

speed of rotation limit	reference n [1/min]	grease n [1/min]	oil n [1/min]
		4800	5600

operating temperature	max. [°C]	min. [°C]
	120	-20

bearing clearance	radial min. [µm]	max. [µm]
	40	70

material specification

description	material	DIN/ISO	hardness
Inner ring	100Cr6	683-17	58-65
Outer ring	100Cr6	683-17	58-65
Cylindrical rollers	100Cr6	683-17	58-65
Cage	PA66 + GF25		

All information in this document was provided and checked carefully. Nevertheless, we can not assume any liability for incomplete or faulty information.