Hans Saurer Kugellager AG
Niederfeld 38
CH-9320 Stachen

data sheet

general data/description


created: 11.07.2016 / 03 page: 1 / 1

article NJ 2205 E M **Art-No.** 47660 **brand** SKA **weight/kg** 0.157

description

NJ	Design
2205	Size
E	Reinforced version
M	Brass cage, roller centered

dimensions and tolerances



dimension	Description	[mm]	tolerance [µm]	DIN/ISO
d	nominal inner diameter	25	0 / -10	620-2
D	nominal outer diameter	52	0 / -13	620-2
B	width	18	0 / -120	620-2
Fw	inner enveloping circle diameter	31.5	0 / 15	5412-1
r1s min.	minimal chamfer dimension	1		5412-1
r2s min.	minimal chamfer dimension	0.6		5412-1
s	axial displacement	~ 1.5		
d1	inner shoulder diameter	~ 34.9		
D1	outer shoulder diameter	~ 44		
E	raceway diameter outer ring	46.5		

calculation and operating data

load ratings	dynamic C [N]	fatique load limit load Cu [N]	DIN/ISO	static Co [N]	DIN/ISO
	34900	4300	281	34800	76

speed of rotation limit	reference n [1/min]	grease n [1/min]	oil n [1/min]
		12000	14000

operating temperature	max. [°C]	min. [°C]
	120	-20

bearing clearance	radial min. [µm]	max. [µm]
	20	45

material specification

description	material	DIN/ISO	hardness
Inner ring	100Cr6	683-17	58-65
Outer ring	100Cr6	683-17	58-65
Cylindrical rollers	100Cr6	683-17	58-65
Cage	CuZn40Pb2		

All information in this document was provided and checked carefully. Nevertheless, we can not assume any liability for incomplete or faulty information.