general data/description


created: 15.03.2018 / 02 page: 1 / 2

article 32308 **Art-No.** 48828 **brand** SKA **weight/kg** 1.03

description
32308 Size

remark Description according ISO 355: T 2FD 040

dimensions and tolerances



dimension	Description	[mm]	tolerance [µm]	DIN/ISO
d	nominal inner diameter	40	0 / -12	620-2
D	nominal outer diameter	90	0 / -18	620-2
B	inner ring width	33	0 / -120	620-2
C	outer ring width	27	0 / -120	620-2
T	bearing width	35.25	0 / 200	720
r1s min.	minimal chamfer dimension	2		720
r2s min.	minimal chamfer dimension	2		720
r3s min.	minimal chamfer dimension	1.5		720
r4s min.	minimal chamfer dimension	1.5		720
d1	flange diameter of the inner ring	63.2	0 / -300	
a	load application point	23.3		
Da min.	mounting dimension	73		
Da max.	mounting dimension	81		
da max.	mounting dimension	50		
Db min.	mounting dimension	82		
db min.	mounting dimension	49		
Ca min.	mounting dimension	4		
Cb min.	mounting dimension	8		
ra max.	mounting dimension	1.5		
rb max.	mounting dimension	2		
e	calculation factor	0.35		
Y	calculation factor	1.7		
Y0	calculation factor	0.9		

Hans Saurer Kugellager AG
Niederfeld 38
CH-9320 Stachen

article 32308 **Art-No.** 48828

calculation and operating data

load ratings	dynamic C [N]	fatique load limit load Cu [N]	DIN/ISO	static Co [N]	DIN/ISO
	120000	17300	281	147000	76

speed of rotation limit	reference n [1/min]	grease n [1/min]	oil n [1/min]
		4400	5900

operating temperature	max. [°C]	min. [°C]
	120	-20

material specification

description	material	DIN/ISO	hardness
Inner ring	100Cr6	683-17	58-65
Outer ring	100Cr6	683-17	58-65
Tapered rollers	100Cr6	683-17	58-65
Cage	Sheet steel		

All information in this document was provided and checked carefully. Nevertheless, we can not assume any liability for incomplete or faulty information.