general data/description

created: 26.06.2018 / 02 page: 1 / 2

article 3811 B TN 2RS NS7 **Art-No.** 49376 **brand** SKA **weight/kg** 0.09

remark Y-factors: Y1: Fa/Fr <= e / Y2: Fa/Fr > e.


description

B	Pressure angle
TN	Plastic cage
2RS	Sealing washers on both sides, touching

greasing

NS7	KYODO YUSHI MULTEMP SRL

dimensions and tolerances



dimension	Description	[mm]	tolerance [µm]	DIN/ISO
d	nominal inner diameter	55	0 / -15	620-2
D	nominal outer diameter	72	0 / -13	620-2
B	width	13	0 / -150	620-2
rs min.	minimal chamfer dimension	0.3		
alpha	contact angle	30°		
a	load application point	~40.16		
e	calculation factor	0.8		281
Y1	calculation factor	0.78		281
Y2	calculation factor	1.24		281
Y0	calculation factor	0.66		76
X	calculation factor	0.63		281

calculation and operating data

load ratings	dynamic C [N]	fatique load limit load Cu [N]	DIN/ISO	static Co [N]	DIN/ISO
	9810	673	281	12900	76

speed of rotation limit	reference n [1/min]	grease n [1/min]	oil n [1/min]
		4300	

operating temperature	max. [°C]	min. [°C]
	120	-20

bearing clearance	axial min. [µm]	max. [µm]
	13	36

Hans Saurer Kugellager AG
Niederfeld 38
CH-9320 Stachen

article 3811 B TN 2RS NS7 **Art-No.** 49376

material specification

description	material	DIN/ISO	hardness
Inner ring	100Cr6	683-17	58-65
Outer ring	100Cr6	683-17	58-65
Balls	100Cr6	683-17	58-66
Cage	PA66+GF25		
Sealing washers	St12/NBR		

All information in this document was provided and checked carefully. Nevertheless, we can not assume any liability for incomplete or faulty information.