Hans Saurer Kugellager AG
Niederfeld 38
CH-9320 Stachen

data sheet

general data/description


created: 13.06.2018 / 01 page: 1 / 1

article NUP 210 E TVP2 **Art-No.** 49483 **brand** SKA **weight/kg** 0.475

description

NUP	Design
210	Size
E	Reinforced version
TVP2	Plastic cage

dimensions and tolerances



dimension	Description	[mm]	tolerance [µm]	DIN/ISO
d	nominal inner diameter	50	0 / -12	620-2
D	nominal outer diameter	90	0 / -15	620-2
B	width	20	0 / -120	620-2
Fw	inner enveloping circle diameter	59.5	0 / 20	5412-1
r1s min.	minimal chamfer dimension	1.1		5412-1
r2s min.	minimal chamfer dimension	1.1		5412-1
d1	inner shoulder diameter	~ 64		
D1	outer shoulder diameter	~ 78.3		
B1	flange width	4		5412-1
E	raceway diameter outer ring	81.5		5412-1

calculation and operating data

load ratings	dynamic C [N]	fatique load limit load Cu [N]	DIN/ISO	static Co [N]	DIN/ISO
	63600	8600	281	68900	76

speed of rotation limit	reference n [1/min]	grease n [1/min]	oil n [1/min]
		6300	7500

operating temperature	max. [°C]	min. [°C]
	120	-20

bearing clearance	radial min. [µm]	max. [µm]
	30	60

material specification

description	material	DIN/ISO	hardness
Inner ring	100Cr6	683-17	58-65
Outer ring	100Cr6	683-17	58-65
Cage	PA66 + GF25		
Cylindrical rollers	100Cr6	683-17	58-65
Flange disc	100Cr6	683-17	58-65

All information in this document was provided and checked carefully. Nevertheless, we can not assume any liability for incomplete or faulty information.