Hans Saurer Kugellager AG
Niederfeld 38
CH-9320 Stachen

data sheet

general data/description


created: 09.11.2018 / 01 page: 1 / 1

article NJ 2207 E TVP2 HQS **Art-No.** 49789 **brand** SKA **weight/kg** 0.395

description

NJ	Design
2207	Size
E	Reinforced version
TVP2	Plastic cage
HQS	Material

dimensions and tolerances



dimension	Description	[mm]	tolerance [µm]	DIN/ISO
d	nominal inner diameter	35	0 / -12	620-2
D	nominal outer diameter	72	0 / -13	620-2
B	width	23	0 / -120	620-2
r1s min.	minimal chamfer dimension	1.1		5412-1
r2s min.	minimal chamfer dimension	0.6		5412-1
Fw	inner enveloping circle diameter	44	0 / 15	5412-1
s	axial displacement	~ 0.7		
d1	inner shoulder diameter	~ 48.5		
D1	outer shoulder diameter	~ 60.5		
E	raceway diameter outer ring	64		5412-1

calculation and operating data

load ratings	dynamic C [N]	fatique load limit load Cu [N]	DIN/ISO	static Co [N]	DIN/ISO
	59800	7800	281	63000	76

speed of rotation limit	reference n [1/min]	grease n [1/min]	oil n [1/min]
		8500	10000

operating temperature	max. [°C]	min. [°C]
	120	-20

bearing clearance	radial min. [µm]	max. [µm]
	25	50

material specification

description	material	DIN/ISO	hardness
Inner ring	100Cr6	683-17	58-65
Outer ring	100Cr6	683-17	58-65
Cylindrical rollers	100Cr6	683-17	58-65
Cage	PA66 + GF25		

All information in this document was provided and checked carefully. Nevertheless, we can not assume any liability for incomplete or faulty information.