Hans Saurer Kugellager AG
Niederfeld 38
CH-9320 Stachen

data sheet

general data/description

created: 13.12.2018 / 01

article RAE 15 NPP HA2 **Art-No.** 50040 **brand** SKA **weight/kg** 0.12

remark Rotational speed is reference value for shaft tolerance h7. Also depending on load and seal.


description

RAE	Design
15	Size
NPP	Seals

greasing

HA2	HANGU2#, GREAT WALL MOTOR BEARING GREASE

dimensions and tolerances



dimension	Description	[mm]	tolerance [µm]	DIN/ISO
d	nominal inner diameter	15	0 / 15	626-1
d1 max.	clamping ring outer diameter	28.6		626-1
B	inner ring width	19.1	0 / -120	626-1
B1	total width	28.6		626-1
B2	clamping ring width	13.5		626-1
D	nominal outer diameter	40	0 / -11	620-2
C	outer ring width	12	0 / -120	620-2

article RAE 15 NPP HA2 **Art-No.** 50040

dimension	Description	[mm]	tolerance [µm]	DIN/ISO
S	swing axle distance	6		626-1
rs min.	minimal chamfer dimension	0.5		
G	thread	M6x0.75		
sw	wrench size	3		

calculation and operating data

load ratings	dynamic C [N]	fatique load limit load Cu [N]	DIN/ISO	static Co [N]	DIN/ISO
	9550	240	281	4760	76

speed of rotation limit	reference n [1/min]	grease n [1/min]	oil n [1/min]
		6000	

operating temperature	max. [°C]	min. [°C]
	120	-20

bearing clearance	radial min. [µm]	max. [µm]
	11	25

material specification

description	material	DIN/ISO	hardness
Inner ring	100Cr6	683-17	58-65
Outer ring	100Cr6	683-17	58-65
Balls	100Cr6	683-17	58-65
Cage	Sheet steel		
Seals	Sheet steel/NBR		
Clamping ring	C45		

All information in this document was provided and checked carefully. Nevertheless, we can not assume any liability for incomplete or faulty information.