Hans Saurer Kugellager AG
Niederfeld 38
CH-9320 Stachen

data sheet

general data/description

created: 04.03.2020 / 01 page: 1 / 1


article GE 25 ES **Art-No.** 50334 **brand** SKA **weight/kg** 0.11

remark All data according to manufacturer catalog.

description

GE	Design
25	Size
ES	Sliding pair, requiring maintenance

dimensions and tolerances



dimension	Description	[mm]	tolerance [µm]	DIN/ISO
d	nominal inner diameter	25	0 / -10	12240-1
D	nominal outer diameter	42	0 / -11	12240-1
B	inner ring width	20	0 / -120	12240-1
C	outer ring width	16	0 / -240	12240-1
dk	ball diameter	35.5		WERKSNORM
r1s min.	minimal chamfer dimension	0.6		12240-1
r2s min.	minimal chamfer dimension	0.6		12240-1
b	groove width outer ring	3.1		WERKSNORM
b1	groove width inner ring	3.1		WERKSNORM
M	diameter lubrication hole	2		WERKSNORM
alpha	tilt angle	~7°		12240-1

calculation and operating data

load ratings	**dynamic C [N]**	**fatique load limit load Cu [N]**	**DIN/ISO**	**static Co [N]**	**DIN/ISO**
	48000			240000	
operating temperature	**max. [°C]**	**min. [°C]**			
	150	-50			
bearing clearance	**radial min. [µm]**	**max. [µm]**			
	50	100			

material specification

description	material	DIN/ISO	hardness
Inner ring	100Cr6	683-17	58-65
Outer ring	100Cr6	683-17	58-65

All information in this document was provided and checked carefully. Nevertheless, we can not assume any liability for incomplete or faulty information.