Hans Saurer Kugellager AG
Niederfeld 38
CH-9320 Stachen

data sheet

general data/description

created: 10.07.2019 / 02


article B 71900 C T U L P4S **Art-No.** 50581 **brand** SKA **weight/kg** 0.011

remark Tolerance class P4S: dimensional accuracy P4, running accuracy P2, according DIN 620-2.

description

B	Design
71900	size
C	Pressure angle
T	Hard tissue cage
U	Universally pairable
L	Slight preload
P4S	Tolerance class

dimensions and tolerances



dimension	Description	[mm]	tolerance [µm]	DIN/ISO
d	nominal inner diameter	10	0 / -4	620-2
D	nominal outer diameter	22	0 / -5	620-2
B	width	6	0 / -40	620-2
r1s min.	minimal chamfer dimension	0.3		616
r2s min.	minimal chamfer dimension	0.3		616
a	load application point	5.1		
alpha	contact angle	15°		
E dT min.	Minimum diameter injection pitch	14.4		
E dT max.	Maximum diameter injection pitch	15		
Fv	pretension [N]	10		
c	axial stiffness [N/µm]	11		
KaE	Lift-off force [N]	31		

calculation and operating data

load ratings	dynamic C [N]	fatique load limit load Cu [N]	DIN/ISO	static Co [N]	DIN/ISO
	3010	75	281	1520	76

speed of rotation limit	reference n [1/min]	grease n [1/min]	oil n [1/min]
		75000	120000

operating temperature	max. [°C]	min. [°C]
	120	-20

article B 71900 C T U L P4S **Art-No.** 50581

material specification

description	material	DIN/ISO	hardness
Inner ring	100Cr6	683-17	58-65
Outer ring	100Cr6	683-17	58-65
Balls	100Cr6	683-17	58-65
Cage	PF		

All information in this document was provided and checked carefully. Nevertheless, we can not assume any liability for incomplete or faulty information.