general data/description

created: 27.10.2022 / 01 page: 1 / 2

article HS 71900 E T 2RSD U L P4S BQ2 **Art-No.** 50854

brand SKA **weight/kg** 0.011

remark Tolerance class P4S: dimensional accuracy P4, running accuracy P2, according DIN 620-2.


description

HS	Design
71900	size
E	Pressure angle
T	Hard tissue cage
2RSD	Sealing washers on both sides, not touching
U	Universally pairable
L	Slight preload
P4S	Tolerance class

greasing

BQ2	KLÜBERQUIET BQ74-73N

dimensions and tolerances



dimension	Description	[mm]	tolerance [µm]	DIN/ISO
d	nominal inner diameter	10	0 / -4	620-2
D	nominal outer diameter	22	0 / -5	620-2
B	width	6	0 / -40	620-2
r1s min.	minimal chamfer dimension	0.3		628-6
r2s min.	minimal chamfer dimension	0.1		628-6
a	load application point	6.7		
alpha	contact angle	25°		
Fv	pretension [N]	11		
c	axial stiffness [N/µm]	21.7		
KaE	Lift-off force [N]	31		

calculation and operating data

load ratings	dynamic C [N]	fatique load limit load Cu [N]	DIN/ISO	static Co [N]	DIN/ISO
	1'860	44	281	840	76

speed of rotation limit	reference n [1/min]	grease n [1/min]	oil n [1/min]
		85'000	

operating temperature	max. [°C]	min. [°C]
	100	-20

Hans Saurer Kugellager AG
Niederfeld 38
CH-9320 Stachen

article HS 71900 E T 2RSD U L P4S BQ2 **Art-No.** 50854

material specification

description	material	DIN/ISO	hardness
Inner ring	100Cr6	683-17	58-65
Outer ring	100Cr6	683-17	58-65
Balls	100Cr6	683-17	58-65
Cage	PF		
Sealing washers	St12/NBR		

All information in this document was provided and checked carefully. Nevertheless, we can not assume any liability for incomplete or faulty information.