Hans Saurer Kugellager AG
Niederfeld 38
CH-9320 Stachen

data sheet

general data/description


created: 20.04.2020 / 01

article 7211 B TVP **Art-No.** 51035 **brand** SKA **weight/kg** 0.635

description

7211	Size
B	Pressure angle
TVP	Plastic cage

dimensions and tolerances



dimension	Description	[mm]	tolerance [µm]	DIN/ISO
d	nominal inner diameter	55	0 / -15	620-2
D	nominal outer diameter	100	0 / -15	620-2
B	width	21	0 / -150	620-2
r1s min.	minimal chamfer dimension	1.5		628-1
r2s min.	minimal chamfer dimension	1		628-1
alpha	contact angle	40°		628-1
a	load application point	~43		
e	calculation factor	1.14		
X0	calculation factor	0.5		
Y0	calculation factor	0.26		
X	calculation factor	0.35		
Y	calculation factor	0.57		

calculation and operating data

load ratings	dynamic C [N]	fatique load limit load Cu [N]	DIN/ISO	static Co [N]	DIN/ISO
	46300	1870	281	36100	76

speed of rotation limit	reference n [1/min]	grease n [1/min]	oil n [1/min]
		5300	7100

operating temperature	max. [°C]	min. [°C]
	120	-20

material specification

description	material	DIN/ISO	hardness
Inner ring	100Cr6	683-17	58-65
Outer ring	100Cr6	683-17	58-65
Balls	100Cr6	683-17	58-65
Cage	PA66+GF25		

All information in this document was provided and checked carefully. Nevertheless, we can not assume any liability for incomplete or faulty information.