Hans Saurer Kugellager AG
Niederfeld 38
CH-9320 Stachen

data sheet

general data/description

created: 01.02.2024 / 04

article 3201 B TN NS7 **Art-No.** 51401 **brand** SKA **weight/kg** 0.063

remark Y-factors: Y1: Fa/Fr <= e / Y2: Fa/Fr > e.


description


3201	Size
B	Pressure angle
TN	Plastic cage

greasing

NS7	KYODO YUSHI MULTEMP SRL

dimensions and tolerances





dimension	Description	[mm]	tolerance [µm]	DIN/ISO
d	nominal inner diameter	12	0 / -8	620-2
D	nominal outer diameter	32	0 / -11	620-2
B	width	15.9	0 / -120	620-2
rs min.	minimal chamfer dimension	0.6		628-3
alpha	contact angle	30°		628-3
a	load application point	~19.1		
Da max.	mounting dimension	28		WERKSNORM
da min.	mounting dimension	16		WERKSNORM
ra max.	mounting dimension	0.6		WERKSNORM
e	calculation factor	0.8		281
Y1	calculation factor	0.78		281
Y2	calculation factor	1.24		281
Y0	calculation factor	0.66		76
X	calculation factor	0.63		281

calculation and operating data

load ratings	**dynamic C [N]**	**fatique load limit load Cu [N]**		**DIN/ISO**	**static Co [N]**	**DIN/ISO**
	10300	290		281	5650	76
speed of rotation limit	**reference n [1/min]**	**grease n [1/min]**	**oil n [1/min]**			
		15000	20000			
operating temperature	**max. [°C]**	**min. [°C]**				
	120	-30				
bearing clearance	**axial min. [µm]**	**max. [µm]**				
	6	23				

article 3201 B TN NS7 **Art-No.** 51401

material specification

description	material	DIN/ISO	hardness
Inner ring	100Cr6	683-17	58-65
Outer ring	100Cr6	683-17	58-65
Balls	100Cr6	683-17	58-66
Cage	PA66+GF25		

All information in this document was provided and checked carefully. Nevertheless, we can not assume any liability for incomplete or faulty information.