general data/description


article B 7206 E T P4S UL **Art-No.** 51999 **brand** SKA **weight/kg** 0.192

remark Tolerance class P4S: dimensional accuracy P4, running accuracy P2, according DIN 620-2.

description

B	Design
7206	Size
E	Pressure angle
T	Hard tissue cage
P4S	Tolerance class
UL	Universally pairable, Slight preload

dimensions and tolerances



dimension	Description	[mm]	tolerance [µm]	DIN/ISO
d	nominal inner diameter	30	0 / -5	620-2
D	nominal outer diameter	62	0 / -7	620-2
B	width	16	0 / -120	620-2
r1s min.	minimal chamfer dimension	1		628-1
r2s min.	minimal chamfer dimension	0.6		628-1
a	load application point	18.8		
alpha	contact angle	25°		628-6
E dT	Diameter injection pitch	42.7		WERKSNORM
Fv	pretension [N]	177		
c	axial stiffness [N/µm]	90.4		
KaE	Lift-off force [N]	518		

calculation and operating data

load ratings	dynamic C [N]	fatique load limit load Cu [N]	DIN/ISO	static Co [N]	DIN/ISO
	24400	732	281	14100	76

speed of rotation limit	reference n [1/min]	grease n [1/min]	oil n [1/min]
		22000	36000

operating temperature	max. [°C]	min. [°C]
	100	-30

material specification

description	material	DIN/ISO	hardness
Inner ring	100Cr6	683-17	58-65
Outer ring	100Cr6	683-17	58-65
Balls	100Cr6	683-17	58-65
Cage	PF		

Hans Saurer Kugellager AG
Niederfeld 38
CH-9320 Stachen

article B 7206 E T P4S UL **Art-No.** 51999

All information in this document was provided and checked carefully. Nevertheless, we can not assume any liability for incomplete or faulty information.