Hans Saurer Kugellager AG
Niederfeld 38
CH-9320 Stachen

general data/description

created: 24.03.2022 / 01 page: 1 / 2

article KRV 32 PP OP SK LX3 **Art-No.** 52310 **brand** SKA **weight/kg** 0.098

remark Load ratings calculated according norms for rolling bearings. Rotational speed for F < 0.05 C0rw.


description

KRV	Design
32	Size
PP	Seals on both sides
OP	Optimized profile
SK	Hexagon socket

greasing

LX3	SHELL GADUS S3 V220C 2

dimensions and tolerances



dimension	Description	[mm]	tolerance [µm]	DIN/ISO
d1	shaft diameter	12	0 / -18	ISO 7063
d2	inner shoulder diameter	23.2		
D	nominal outer diameter	32	0 / -50	WERKSNORM
C	outer ring width	14	0 / -120	620-2
C1	distance	0.6		ISO 7063
B	length	40	-300 / 600	WERKSNORM
B1 max.	width	15.2		ISO 7063
B2	shaft lenght	25		ISO 7063

article KRV 32 PP OP SK LX3 **Art-No.** 52310

dimension	Description	[mm]	tolerance [µm]	DIN/ISO
B3	distance lubrication hole	6		ISO 7063
rs min.	minimal chamfer dimension	0.6		ISO 7063
G	thread	M12x1.5		ISO 7063
LG	thread length	13		ISO 7063
sw/sw1	wrench size	6		
R	radius outer ring	OP		
d3	diameter lubrication hole	2.5		
Crw [N]	Effective dynamic load rating	10600		
C0rw [N]	Effective static load rating	12800		
Curw [N]	Effective fatigue limit load	1200		

calculation and operating data

load ratings	dynamic C [N]	fatique load limit load Cu [N]	DIN/ISO	static Co [N]	DIN/ISO
	13000	2410	281	17600	76

speed of rotation limit	reference n [1/min]	grease n [1/min]	oil n [1/min]
		2100	

operating temperature	max. [°C]	min. [°C]
	100	-20

bearing clearance	radial min. [µm]	max. [µm]
	10	35

material specification

description	material	DIN/ISO	hardness
Outer ring	100Cr6	683-17	58-65
Roller stud	16CrMo4		
Needle rollers	100Cr6	683-17	58-65
Thrust washer	100Cr6	683-17	58-65
Seals	PA66		

All information in this document was provided and checked carefully. Nevertheless, we can not assume any liability for incomplete or faulty information.