Hans Saurer Kugellager AG
Niederfeld 38
CH-9320 Stachen

data sheet

general data/description

created: 28.07.2022 / 01

article UCFL 203 UZ1 **Art-No.** 52497 **brand** SKA **weight/kg** 0.47

description


UCFL	Design
203	Size

greasing

UZ1	UNIVERSAL ZR-LN1

remark Rotational speed is reference value for shaft tolerance h7. Also depending on load and seal.

dimensions and tolerances



dimension	Description	[mm]	tolerance [µm]	DIN/ISO
d	nominal inner diameter	17	0 / 15	626-1
D	nominal outer diameter	47	0 / -11	620-2
B	inner ring width	31	0 / -120	626-1
C	outer ring width	17	0 / -120	626-1
S	swing axle distance	12.7		626-1
A	housing height	25.5		626-2
A1	flange thickness	11		626-2
A2	effect distance	15	-500 / 500	626-2
A3	total width	33.3		
J	hole spacing	90	-500 / 500	626-2
H	housing length	113		
L	housing width	60		626-2
N	hole diameter	12		
sw	wrench size	2.5		
G	thread	M5x0.8		

Hans Saurer Kugellager AG
Niederfeld 38
CH-9320 Stachen

article UCFL 203 UZ1 **Art-No.** 52497

calculation and operating data

load ratings	**dynamic C [N]**	**fatique load limit load Cu [N]**		**DIN/ISO**	**static Co [N]**	**DIN/ISO**
	12800	340		281	6590	76
speed of rotation limit	**reference n [1/min]**	**grease n [1/min]**	**oil n [1/min]**			
		6000				
operating temperature	**max. [°C]**	**min. [°C]**				
	120	-20				
bearing clearance	**radial min. [µm]**	**max. [µm]**				
	11	25				

material specification

description	material	DIN/ISO	hardness
Inner ring	100Cr6	683-17	58-65
Outer ring	100Cr6	683-17	58-65
Balls	100Cr6	683-17	58-65
Cage	Sheet steel		
Seals	Sheet steel/NBR		
Centrifugal disc	Sheet steel		
Housing	GG20		

All information in this document was provided and checked carefully. Nevertheless, we can not assume any liability for incomplete or faulty information.