Hans Saurer Kugellager AG
Niederfeld 38
CH-9320 Stachen

data sheet

general data/description

created: 19.03.2024 / 01 page: 1 / 1

article HK 0608 BI2 **Art-No.** 53552 **brand** SKA **weight/kg** 0.0021

remark For cup needle bearings the enveloping circle diameter Fw can only be checked in installed condition.


description

HK	Design
0608	Size

greasing

BI2	KLÜBER ISOFLEX TOPAS L32

dimensions and tolerances



dimension	Description	[mm]	tolerance [µm]	DIN/ISO
Fw	inner enveloping circle diameter	6	10 / 28	618
D	nominal outer diameter	10		618
C	width	8	-300 / 0	618
rs min.	minimal chamfer dimension	0.4		618

calculation and operating data

load ratings	dynamic C [N]	fatique load limit load Cu [N]	DIN/ISO	static Co [N]	DIN/ISO
	2540	255	281	2170	76

speed of rotation limit	reference n [1/min]	grease n [1/min]	oil n [1/min]
		20000	32000

operating temperature	max. [°C]	min. [°C]
	120	-60

material specification

description	material	DIN/ISO	hardness
Sleeve	Sheet steel		
Needle rollers	100Cr6	683-17	58-65
Cage	Sheet steel		

All information in this document was provided and checked carefully. Nevertheless, we can not assume any liability for incomplete or faulty information.