general data/description

created: 22.09.2026 / 01 page: 1 / 2

article 3308 B TN 2RS LX5 **Art-No.** 55214

brand SKA **weight/kg** 1.05

remark Y-factors: Y1: Fa/Fr <= e / Y2: Fa/Fr > e.


description


3308	Size
B	Pressure angle
TN	Plastic cage
2RS	Sealing washers on both sides, touching

greasing

LX5	SHELL GADUS S2 V100 3

dimensions and tolerances





dimension	Description	[mm]	tolerance [µm]	DIN/ISO
d	nominal inner diameter	40	0 / -12	620-2
D	nominal outer diameter	90	0 / -15	620-2
B	width	36.5	0 / -120	620-2
rs min.	minimal chamfer dimension	1.5		628-3
alpha	contact angle	30°		628-3
a	Lastabstand	~53.3		
Da max.	mounting dimension	80.5		WERKSNORM
da min.	mounting dimension	50.3		WERKSNORM
ra max.	mounting dimension	1.5		5418
e	calculation factor	0.8		281
Y1	calculation factor	0.78		281
Y2	calculation factor	1.24		281
Y0	calculation factor	0.66		76
X	calculation factor	0.63		281

Hans Saurer Kugellager AG
Niederfeld 38
CH-9320 Stachen

article 3308 B TN 2RS LX5 **Art-No.** 55214

calculation and operating data

load ratings	**dynamic C [N]**	**fatique load limit load Cu [N]**		**DIN/ISO**	**static Co [N]**	**DIN/ISO**
	67000	2280		281	43900	76
speed of rotation limit	**reference n [1/min]**	**grease n [1/min]**	**oil n [1/min]**			
		5000				
operating temperature	**max. [°C]**	**min. [°C]**				
	120	-30				
bearing clearance	**axial min. [µm]**	**max. [µm]**				
	9	29				

material specification

description	material	DIN/ISO	hardness
Inner ring	100Cr6	683-17	58-65
Outer ring	100Cr6	683-17	58-65
Balls	100Cr6	683-17	58-66
Cage	PA66+GF25		
Sealing washers	St12/NBR		

All information in this document was provided and checked carefully. Nevertheless, we can not assume any liability for incomplete or faulty information.